## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Lampemagasinet

Supplier's address: -

## Model identifier: SMAL ARMATUR 40W

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	-				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

	riouuci parameters					
Parameter		Value	Parameter	Value		
General product parameters:						
0,	ption in on-mo- ), rounded up to ger	40	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	5 200 in Wi- de cone (120°)	Correlated colour temperature, roun- ded to the nearest 100 K, or the range of correlated colour temperatures, roun- ded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	40,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	_		
<sub>et</sub> ) for CLS, expr	ndby power (P <sub>n-</sub> essed in W and second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-va- lues that can be set	80		
Outer di- mensions wit- hout sepa- rate control gear, lighting	Height Width Depth	61 72 1 180	Spectral power dis- tribution in the ran- ge 250 nm to 800 nm, at full-load	See image in last page		

control parts and non-ligh- ting control parts, if any (millimetre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent po- wer (W)	-			
		Chromaticity coordi- nates (x and y)	0,380 0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,98					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

Model placed on the Union market from 01/11/2021.Image: State Sta