## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

30uices						
Supplier's name or trade mark: Lampemagasinet						
Supplier's address: -						
Model identifier: NORDLYS PLAFOND 3 STEG STOR MATT SORT 24W 2700K 2450LM 230V						
Type of light source:						
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		-				
(or other electri	ic interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on-mo- de (kWh/1000 h), rounded up to the nearest integer		24	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 450 in -	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	<u>-</u>		
On-mode power (P <sub>on</sub> ), expressed in W		24,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	-		
Networked standby power (P <sub>n-et</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	<del></del>		
Outer di-	Height	-	Spectral power dis-	See image		
mensions without separate control gear, lighting	Width Depth	-	tribution in the range 250 nm to 800 nm, at full-load	in last page		

control parts and non-ligh- ting control parts, if any (millimetre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent po- wer (W)	-		
		Chromaticity coordinates (x and y)	-		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	-	Survival factor	-		
the lumen maintenance factor	-				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-		

(a)<sub>'-'</sub>: not applicable; (b)<sub>'-'</sub>: not applicable;

Model placed on the Union market from 01/11/2023.



EPREL registration number: 1751398 <a href="https://eprel.ec.europa.eu/qr/17">https://eprel.ec.europa.eu/qr/17</a>

51398

Supplier: Lampemagasinet AS (Importer) Website: www.lampemagasinet.no

**Customer care service:** 

Name: Website:

Email: Phone:

Address: