## **Product Information Sheet**

Networked standby power (P<sub>n</sub>-

et) for CLS, expressed in W and

rounded to the second decimal

Height

Width

Depth

di-

sepa-

control

Outer

hout

rate

mensions wit-

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Lampemagasinet  Supplier's address: -  Model identifier: LM LED 6.5W G125 GLOBE SPIRAL AMBER 2700K 550LUMEN E27 230V DIMBAR Ra85								
					Type of light source:			
					Lighting technology used:	LED	Non-directional or directional:	NDLS
					Light source cap-type	-		
(or other electric interface)								
Mains or non-mains:	MLS	Connected light source (CLS):	No					
Colour-tuneable light source:	No	Envelope:	-					
High luminance light source:	No							
Anti-glare shield:	No	Dimmable:	Yes					
	Product para	ameters						
Parameter	Value	Parameter	Value					
	General product	parameters:						
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	7	Energy efficiency class	G					
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	550 in -	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	<del>-</del>					
On-mode power (P <sub>on</sub> ), expressed in W	6,5	Standby power (P <sub>sb</sub> ), expressed in W	-					

and rounded to the second decimal

Colour rendering in-

dex, rounded to the nearest integer, or

the range of CRI-values that can be set Spectral power dis-

tribution in the ran-

ge 250 nm to 800

nm, at full-load

-...-

See image

in last page

gear, lighting control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent po- wer (W)	-	
		Chromaticity coordinates (x and y)	-	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-	Survival factor	-	
the lumen maintenance factor	-			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-	

(a)'-': not applicable; (b)'-': not applicable;

Model placed on the Union market from 01/11/2023.



**EPREL registration number:** 1745171 https://eprel.ec.europa.eu/qr/17

45171

Supplier: Lampemagasinet AS (Importer) Website: www.lampemagasinet.no

**Customer care service:** 

Name: Website:

Email: Phone:

Address: