## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Sources						
Supplier's name or trade mark: Lampemagasinet						
Supplier's address: -						
Model identifier: LM LED 3.5W T25 AMBER 2000K 270LUMEN E14 230V DIMBAR Ra85						
Type of light so	urce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		E14				
(or other electri	c interface)					
Mains or non-mains:		MLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	Yes		
		Product para	ameters			
Parameter		Value	Parameter	Value		
		General product	parameters:			
Energy consumption in on-mo- de (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		270 in -	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 000		
On-mode power (P <sub>on</sub> ), expressed in W		4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	-		
Networked standby power (P <sub>n-et</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-va- lues that can be set	85		
Outer di-	Height	-	Spectral power dis-	See image		
mensions without separate control gear, lighting	Width Depth	-	tribution in the range 250 nm to 800 nm, at full-load	in last page		

control parts and non-ligh- ting control parts, if any (millimetre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent po- wer (W)	-		
		Chromaticity coordinates (x and y)	-		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	-	Survival factor	-		
the lumen maintenance factor	-				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-		

(a)'-': not applicable; (b)'-': not applicable;

Model placed on the Union market.	国旅游国 公司 (1)
EPREL registration number: 1809165	https://eprel.ec.europa.eu/qr/18 09165
Supplier: Lampemagasinet AS	Website: www.lampemagasinet.no
Customer care service:	
Name:	Website:
Email:	Phone:
Address:	